PATENT COOPERATION TREATY

rom the NTERNATIONAL SEARCHING AUTHO	RITY					
To: SANFORD T. COLB SANFORD T. COLB & CO.		PCT				
P.O. BOX 2273 REHOVOT, ISRAEL 76122		WRI' INTERNATIO	TTEN OPINION OF THE NAL SEARCHING AUTHORITY			
			(PCT Rule 43bis.1)			
		Date of mailing (day/month/year)	09 MAR 2007			
Applicant's or agent's file reference		FOR FURTHER ACTION See paragraph 2 below				
56571			Priority date (day/month/year)			
International application No.	International filing date	1				
PCT/IL06/00453	10 April 2006 (10.04.20	006)	20 April 2005 (20.04.2005)			
International Patent Classification (IPC)	or both national classifica	tion and IPC				
IPC: G06F 11/00(2007.01) USPC: 714/4,6						
Applicant			,			
AXXANA (ISRAEL) LTD.						
1. This opinion contains indications rel	ating to the following ite	ms:				
Box No. I Basis of the						
Box No. II Priority						
Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability						
Box No. IV Lack of unity of invention						
Box No. V Reasoned s applicabili	Box No. V Reasoned statement under Rule 43bis.1(a)(i) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement					
Box No. VI Certain do	cuments cited					
Box No. VII Certain defects in the international application						
Box No. VIII Certain ob	servations on the internat	ional application				
2. FURTHER ACTION						
If a demand for international preliminary examination is made, this opinion will be considered to be a written opinion of the International Preliminary Examining Authority ("IPEA") except that this does not apply where the applicant chooses an Authority other than this one to be the IPEA and the chosen IPEA has notified the International Bureau under Rule 66.1bis(b) that written opinions of this International Searching Authority will not be so considered.						
If this opinion is, as provided above, considered to be a written opinion of the IPEA, the applicant is invited to submit to the IPEA a written reply together, where appropriate, with amendments, before the expiration of 3 months from the date of mailing of Form PCT/ISA/220 or before the expiration of 22 months from the priority date, whichever expires later.						
For further options, see Form PCT/ISA/220.						
3. For further details, see notes to Form PCT/ISA/220.						
Name and mailing address of the ISA/	US Date of com	pletion of this opinion	Authorized officer Michelle L. Ear			
Mail Stop PCT, Attn: ISA/US Commissioner for Patents	Ì	r 2006 (06.12.2006)	Emerson Puente			
P.O. Box 1450 Alexandria, Virginia 22313-1450			Telephone No. (571) 272-3652			

Facsimile No. (571) 273-3201
Form PCT/ISA/237 (cover sheet) (April 2005)

International application No.
PCT/IL06/00453

Box No. I Basis of this opinion
1. With regard to the language, this opinion has been established on the basis of:
the international application in the language in which it was filed
a translation of the international application into, which is the language of a translation furnished for the purposes of international search (Rules 12.3(a) and 23.1(b)).
With regard to any nucleotide and/or amino acid sequence disclosed in the international application and necessary to the claimed invention, this opinion has been established on the basis of:
a. type of material
a sequence listing
table(s) related to the sequence listing
b. format of material
on paper
in electronic form
c. time of filing/furnishing
contained in the international application as filed.
filed together with the international application in electronic form.
furnished subsequently to this Authority for the purposes of search.
In addition, in the case that more than one version or copy of a sequence listing and/or table(s) relating thereto has been filed or furnished, the required statements that the information in the subsequent or additional copies is identical to that in the application as filed or does not go beyond the application as filed, as appropriate, were furnished.
4. Additional comments:
·

Form PCT/ISA/237(Box No. I) (April 2005)

International application No. PCT/IL06/00453

tement Novelty (N) Inventive step (IS) Industrial applicability (IA)	Claims Claims Claims	NONE			YES NO
Inventive step (IS)	Claims Claims	NONE			
	Claims				
	Claims				YE
Industrial applicability (IA)					NO
	Claims	Claims 1-41			YE
	Claims	NONE			_NO
ations and explanations: See Continuation Sheet				•	
•			•		
•					
	•				
	•		•		
		•			
•				-	

Form PCT/ISA/237 (Box No. V) (April 2005)

International application No. PCT/IL06/00453

Supplemental Box	
Supplemental Dox	
In case the space in any of the preceding boxes is not sufficient.	
In case the enges in any of the Drecelling Doxes is not sufficient.	
III Case the space in any or the brosseries and a second	
	

V. 2. Citations and Explanations:

Claims 1-5,7-10,12-33, and 34-41 lack an inventive step under PCT Article 33(3) as being obvious over US Patent No. 6,389,552 of Hamilton et al referred hereinafter "Hamilton" in view of Patent Application Publication 2003/0097607 of Bessire.

In regards to claims 1,22,23,24, and 41 Hamilton discloses:

accepting data for storage from one or more data sources (see column 2 lines 45-55)

sending the data for storage in a primary storage device and in a secondary storage device (see column 2 lines 45-55) when an event damaging at least some of the data in the primary storage device occurs, reconstructing the data using at least part of the data stored in the secondary storage device (see column 3 lines 25-33)

However, Hamilton fails to explicitly disclose:

while awaiting an indication of successful storage of flag data in the secondary storage device, temporarily storing a record associated with the data in a disaster-proof storage unit adjacent to the primary storage device and using the record stored in the disaster proof storage unit for reconstruction during event damaging.

Bessire discloses while awaiting an indication of successful storage of flag data in the secondary storage device, temporarily storing a record associated with the data in a disaster-proof storage unit adjacent to the primary storage device and using the record stored in the disaster proof storage unit for reconstruction during event damaging (see page 3-4 paragraph 32 and 38).

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton and Bessire such that while awaiting an indication of successful storage of flag data in the secondary storage device, temporarily storing a record associated with the data in a disaster-proof storage unit adjacent to the primary storage device and using the record stored in the disaster proof storage unit for reconstruction during event damaging. A person of ordinary skill in the art would have been motivated to combine the teachings because Hamilton is concerned with recovering data during a disaster (see column 3 lines 53-55) and temporarily storing a record associated with the data in a disaster-proof storage unit, as per teachings of Bessire, enables recovery of data being transferred during a failure without having the data source retransmit the data (see page 4 paragraph 38).

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

In regards to claim 2, Bessire discloses:

sending an acknowledgement to the one or more data sources responsively to a successful caching of the record in the disaster-proof storage unit, without waiting to receive the indication of the successful storage of the data in the secondary storage device, so as to reduce a transaction latency associated with the storage of the data (see page 4 paragraph 38).

In regards to claim 3, Bessire discloses:

wherein temporarily storing the record comprises receiving an acknowledgement from the secondary storage device acknowledging the successful storage of the data in the secondary storage device, and deleting the record from the disaster-proof storage unit responsively to the acknowledgement (see page 4 paragraph 38).

In regards to claim 4, Bessire discloses:

wherein reconstructing the data comprises retrieving the disaster-proof storage unit following the event, extracting the record from the disaster proof storage unit and writing the data associated with the record to the secondary storage device (see page 3 paragraph 32).

In regards to claim 5, Bessire discloses:

wherein writing the data comprises remotely connecting the disaster-proof storage unit to the secondary storage device (see page 3 paragraph 32).

In regards to claim 7, Bessire discloses:

detecting the event using a detection mechanism in the disaster proof storage unit and modifying operations of the disaster proof storage unit responsive to detecting the event (see page 3 paragraph 32).

In regards to claim 8, Bessire discloses:

wherein the event comprises detecting at least one of a loss of external power supply and communication failure at the disaster proof storage unit (see page 3 paragraph 32).

In regards to claim 9, Hamilton discloses:

wherein modifying the operation comprises transmitting the record from the disaster-proof storage unit over a wireless communication link (see column 2 lines 35-40).

In regards to claim 10, Bessire discloses:

wherein temporarily storing the record comprises storing the record in two or more disaster proof storage units, wherein transmitting the record comprises transmitting two or more different parts of the record respectively from the two or more disaster proof-storage units over respective links so as to shorten transmission time of the record (see page 3 paragraph 31)

Furthermore, Hamilton discloses using a wireless link (see column 2 lines 35-40). In regards to claims 12 and 25, Hamilton discloses: sensing an environment condition using an environmental sensor, predicting the event responsively to the sensed environmental conditions (see column 3 lines 23-33).

Bessire also discloses after predicting the event, transmitting the record from the disaster-proof storage unit using at least one of a wired connection and a wireless connection (see page 3 paragraph 32).

In regards to claim 13, Hamilton discloses: wherein sensing the environmental condition comprises accepting a manual indication from a user that indicates the event (see column 3 lines 1-15).

In regards to claim 14, Bessire discloses:

wherein temporarily storing the record comprises sending an acknowledgement message responsively to a successful storage of the record in the disaster-proof storage unit, and comprising, after predicting the event, refraining from sending subsequent acknowledgement messages so as to avoid accepting additional data from the one or more data sources (see page 4 paragraph 38).

In regards to claim 15, Hamilton discloses:

refraining from sending subsequent data for storage in primary storage device (see column 3 lines 25-33).

In regards to claim 16. Bessire discloses:

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

after predicting the event, temporarily storing in the disaster-proof storage unit only subsequent records associated with data originating from a subset of the one or more data sources (see page 4 paragraph 38).

In regards to claim 17, Bessire discloses:

wherein temporarily storing the record comprises avoiding exceeding a memory capacity in the disaster-proof storage unit by matching the memory capacity with at least one of a maximum allowed size of data pending for acknowledgement by the second storage device and a maximum number of write commands pending for storage in the secondary storage device (see page 4 paragraph 38).

In regards to claim 18, Bessire discloses:

wherein temporarily storing the record comprises including in the record additional information related to the data, the additional information comprising at least one of an address of an originating data source, an address of the primary storage device, a time stamp indicating an acceptance time of the data and a storage address intended for the data in the primary storage device. Bessire disclose transmitting write request to storage (see page 4 paragraph 38). In order to know where in storage to write data, the data must include storage address information.

In regards to claim 19, Hamilton discloses:

accepting data for storage from one or more data sources (see column 2 lines 45-55) sending the data for storage in a storage device (see column 2 lines 45-55)

However, Hamilton fails to disclose:

temporarily storing records associated with at least a part of the data that is relevant to investigation of disaster events using the records stored in the disaster-proof storage unit and when an event damaging at least some of the data in the storage device occurs, investigating

temporarily storing records associated with at least a part of the data that is relevant to investigation of disaster events using the records stored in the disaster-proof storage unit and when an event damaging at least some of the data in the storage device occurs, investigating the event (see page 3-4 paragraph 32 and 38)

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton and Bessire temporarily storing records associated with at least a part of the data that is relevant to investigation of disaster events using the records stored in the disaster-proof storage unit and when an event damaging at least some of the data in the storage device occurs, investigating the event (see page 3-4 paragraph 32 and 38). A person of ordinary skill in the art would have been motivated to combine the teachings because Hamilton is concerned with recovering data during a disaster (see column 3 lines 53-55) and temporarily storing a record associated with the data in a disaster-proof storage unit, as per teachings of Bessire, enables recovery of data being transferred during a failure without having the data source retransmit the data (see page 4 paragraph 38).

In regards to claim 20, Bessire discloses:

wherein the at least part of the data that is relevant to investigation of disaster events comprises at least one of surveillance images, access control information, and data originating from a telephony system. Bessire discloses storing write I/O request, indicating access control information (see page 4 paragraph 38).

In regards to claim 21, Bessire discloses:

wherein at least part of the data that is relevant to investigation of disaster of events comprises data accepted at a time immediately preceding an occurrence of the event (see page 4 paragraph 38).

In regards to claim 26, Hamilton discloses:

a disaster-proof storage unit, which comprises:

a disaster-proof enclosure, which is arranged to protect components contained therein against disaster events (see column 2 lines 45-55)

control unit, which is arranged, when an event damaging at least some of the data in the primary storage device occurs, to provide the record so as to enable reconstruction of the data using at least part of the data stored in the secondary storage device (see column 3 lines 25-33).

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

a sensor, which is arranged to sense an environmental condition in a vicinity of the primary storage device (see column 3 lines 23-33)

However, Hamilton fails to explicitly disclose:

a memory device contained in the enclosure, which is arranged to temporarily hold a record associated with the data while awaiting an indication of successful storage of the data in the secondary storage device and using the record stored in the memory device to enable reconstruction, and a protection processor, which is arranged to predict the event responsively to the sensed environmental condition and, responsively to predicting the event, to instruct the disaster-proof storage unit to transmit the record so as to protect the data. Bessire discloses a memory device contained in the enclosure, which is arranged to temporarily hold a record associated with the data while awaiting an indication of successful storage of the data in the secondary storage device and using the record stored in the memory device to enable reconstruction, and a protection processor, which is arranged to predict the event responsively to the sensed environmental condition and, responsively to predicting the event, to instruct the disaster-proof storage unit to transmit the record so as to protect the data (see page 3-4 paragraph 32 and 38).

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton and Bessire to use a memory device contained in the enclosure, which is arranged to temporarily hold a record associated with the data while awaiting an indication of successful storage of the data in the secondary storage device and using the record stored in the memory device to enable reconstruction, and a protection processor, which is arranged to predict the event responsively to the sensed environmental condition and, responsively to predicting the event, to instruct the disaster-proof storage unit to transmit the record so as to protect the data. A person of ordinary skill in the art would have been motivated to combine the teachings because Hamilton is concerned with recovering data during a disaster (see column 3 lines 53-55) and temporarily storing a record associated with the data in a disaster-proof storage unit, as per teachings of Bessire, enables recovery of data being transferred during a failure without having the data source retransmit the data (see page 4 paragraph 38).

In regards to claim 27, Bessire discloses:

wherein the control unit is arranged to delete the record from the memory device responsively to an acknowledgement from the secondary storage device acknowledging the successful storage of the data in the secondary storage device (see page 4 paragraph 38).

In regards to claim 28, Hamilton discloses:

wherein the control unit is arranged to communicate with the secondary storage device in order to provide the record so as to reconstruct the data (see column 3 lines 1-15).

In regards to claim 29, Bessire discloses:

wherein the memory device comprises at least one of a non-volatile memory and a removable memory (see page 3 paragraph 32).

In regards to claim 30, Bessire discloses:

wherein the control unit comprises a detection mechanism for detecting the event, and wherein the control unit is arranged to modify operation of the disaster-proof storage unit responsively to detecting the event (see page 3 paragraph 32).

In regards to claim 31, Bessire discloses:

wherein the detection mechanism is arranged to detect at least one of a loss of external electrical power supply and a communication failure at the disaster proof-storage unit (see page 3 paragraph 32).

In regards to claim 32, Hamilton discloses:

wherein the disaster-proof storage unit further comprises a wireless transmitter, which is arranged to transmit the record from the disaster-proof storage unit responsively to detecting the event (see column 2 lines 35-40)

In regards to claim 33, Bessire discloses:

wherein the disaster-proof storage unit is one of two or more disaster proof storage units, which are arranged to transmit respectively two or more different parts of the record over respective links so as to shorten transmission time of the record (see page 3 paragraph 31). Furthermore, Hamilton discloses using a wireless link (see column 2 lines 35-40). In regards to claim 35, Bessire discloses: wherein the record comprises additional information related to the data, the additional information comprising at least one of an address of an originating data source, an address of the primary storage device, a time stamp indicating an acceptance time of the data and a storage address intended for the data in the primary storage device. Bessire disclose transmitting write request to storage (see page 4 paragraph 38). In order to know where in storage to write data, the data must include storage address information.

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

In regards to claim 36, Hamilton discloses:

wherein the sensor is arranged to accept a manual indication from a user so as to predict the event (see column 3 lines 1-15).

In regards to claim 37, Bessire discloses:

wherein the data is accepted from one or more data sources, and wherein protection processor is arranged to send an acknowledgement message responsively to a successful storage of the record in the disaster-proof storage unit, and to refrain from sending subsequent acknowledgement messages so as to avoid accepting additional data from the one or more data sources (see page 4 paragraph 38).

In regards to claim 38, Bessire discloses:

wherein the data is accepted from one or more data sources, and wherein the protection processor is arranged to control a rate of the data accepted from the one or more data sources after predicting the event (see column 3 lines 25-33

In regards to claim 39, Bessire discloses:

wherein the data is accepted form one or more data sources, and wherein the protection processor is arranged to send for temporary storage in the disaster-proof storage only subsequent records associated with data originating from a subset of the one or more data sources after predicting the event (see page 4 paragraph 38).

In regards to claim 40, Bessire discloses:

wherein a capacity of the memory device is matched to a maximum allowed size of data pending for acknowledgement by the secondary storage device so as to avoid exceeding the memory capacity (see page 4 paragraph 38).

Claim 6 lacks an inventive step under PCT Article 33(3) as being obvious over Hamilton in view of Bessire and in further view of 2004/0059844 of Jones et al. referred hereinafter "Jones".

In regards to claim 6, Hamilton in view of Bessire fails to disclose:

wherein the disaster proof storage unit comprises a removable memory device for holding the record, and wherein reconstructing the data comprises when the disaster proof storage unit is damaged by the event, removing the memory device from the disaster proof storage unit and installing the memory device in another unit for readout of the record.

However, Jones discloses in the event of a failure to any portion of the module, the Removable Memory Unit is removed from the module and connected to a new module (see page 2 paragraph 11), indicating wherein the disaster proof storage unit comprises a removable memory device for holding the record, and wherein reconstructing the data comprises when the disaster proof storage unit is damaged by the event, removing the memory device from the disaster proof storage unit and installing the memory device in another unit for readout of the record.

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton, Bessire, and Jones to have a removable memory device for holding the record, and wherein reconstructing the data comprises when the disaster proof storage unit is damaged by the event, removing the memory device from the disaster proof storage unit and installing the memory device in another unit for readout of the record. A person of ordinary skill in the art would have been motivated to combine the teachings because Bessire discloses a memory device for temporarily storing data for recovery (see page 3 paragraph 32), and having a removable memory device constitute a suitable memory device that enables connectable to a new module upon failure of a current module (see page 2 paragraph 11), thus enabling recovery even when there is a failure to the module.

Claims 11 and 34 lack an inventive step under PCT Article 33(3) as being obvious over Hamilton in view of Bessire and in further view of 2003/0204597 of Arakawa et al. referred hereinafter "Arakawa".

In regards to claims 11 and 34, Hamilton in view of Bessire fails to disclose:

wherein modifying the operations comprises transmitting a homing signal from the disaster proof storage unit, so as to enable location and retrieval of the disaster proof storage unit.

However, Arakawa discloses when a storage subsystem detect a failure, sending notification of the failure (see page 8 paragraph 112), indicating wherein modifying the operations comprises transmitting a homing signal from the disaster proof storage unit, so as to enable location and retrieval of the disaster proof storage unit.

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton, Bessire, and Arakawa such that when a storage subsystem detect a failure, sending notification of the failure, indicating wherein modifying the

WRITTEN OPINION OF THE

International application No. PCT/IL.06/00453

INTERNATIONAL SEARCHING AUTHORITY Supplemental Box In case the space in any of the preceding boxes is not sufficient. operations comprises transmitting a homing signal from the disaster proof storage unit, so as to enable location and retrieval of the disaster proof storage unit. A person of ordinary skill in the are art would have been motivated to combine the teachings because Hamilton is concerned with recovering from a failure of a data storage device (see column 3 lines 23-33) and sending notification of a failure, as per teaching of Arakawa (see page 8 paragraph 112), constitute a suitable and known means to identifying a failure of the data storage device, thus enabling recovery from failure. Claims 1-41 meet the criteria set out in PCT Article 33(4), and thus have industrial applicability because the subject matter claimed can be made or used in industry.

PATENT COOPERATION TREATY

rom the NTERNATIO	ONAL SEARCHI	NG AUTHO	RITY			
To:				PCT		
SANFORD T. COLB SANFORD T. COLB & CO.						
P.O. BOX 2273 REHOVOT, ISRAEL 76122			WRIT	TTEN OPINION OF THE		
REHOVOI	, ISRAEL 70122	•		ľ	INTERNATION	NAL SEARCHING AUTHORITY
•				(PCT Rule 43bis.1)		
				Date of mailing (day/month/year) 0 9 MAR 2011		
Applicant's or agent's file reference				FOR FURTHER ACTION See paragraph 2 below		
56571	al application No.		Internatio	nal filing date ('day/month/year)	Priority date (day/month/year)
PCT/IL06/0			10 April 2	2006 (10.04.200	06)	20 April 2005 (20.04.2005)
Internation	al Patent Classific	ation (IPC)				
IPC: C	GO6F 11/00(2007	.01)				
	14/4,6					
Applicant	(IOD AEL) I TD					
AXXANA	(ISRAEL) LTD.					
1. This o	pinion contains in	dications rel	ating to the	following item	s:	
	Box No. I	Basis of the	opinion			
	Box No. II	Priority				
Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability						tive step and industrial applicability
	Box No. IV Lack of unity of invention					
Box No. V Reasoned statement under Rule 43bis.1(a)(i) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement					novelty, inventive step or industrial stement	
Box No. VI Certain documents cited					·	
	Box No. VII	Certain de	fects in the	international ap	plication	
Box No. VIII Certain observations on the international application						
2. FUR	THER ACTIO	N				
If a c	lemand for international Prelimina	ational preli ary Examini ais one to be	ng Author: the IPEA	ity ("IPEA") e and the chosen	veent that this cines	be considered to be a written opinion of the not apply where the applicant chooses an e International Bureau under Rule 66.1 bis(b) ared.
IPEA of Fo	. a written reply to rm PCT/ISA/220	ogether, whe or before the	re appropri e expiration	iate with ameni	amenis, deldie die cai	EA, the applicant is invited to submit to the piration of 3 months from the date of mailing whichever expires later.
For f	urther options, see	Form PCT/	ISA/220.	•		
3. For f	urther details, see	notes to For	m PCT/ISA			
Name an	d mailing address	of the ISA/	US	Date of compl	etion of this opinion	Authorized officer Webblle L. Son
1	Mail Stop PCT, Att Commissioner for I	n: ISA/US Patents	·	06 December	2006 (06.12.2006)	Emerson Puente
	P.O. Box 1450 Alexandria, Virgini	a 22313-1450				Telephone No. (571) 272-3652
Facsimile	No. (571) 273-32	201				
Form PCT	/ISA/237 (cover s	ncer) (April .	2003)			

International application No.
PCT/IL06/00453

Box No	o. I Basis of this opinion
1. With r	regard to the language, this opinion has been established on the basis of:
\boxtimes	the international application in the language in which it was filed
	a translation of the international application into, which is the language of a translation furnished for the purposes of international search (Rules 12.3(a) and 23.1(b)).
2. With inven	regard to any nucleotide and/or amino acid sequence disclosed in the international application and necessary to the claimed tion, this opinion has been established on the basis of:
a.	type of material
	a sequence listing
	table(s) related to the sequence listing
b,	format of material
	on paper
	in electronic form
C.	time of filing/furnishing
	contained in the international application as filed.
	filed together with the international application in electronic form.
	furnished subsequently to this Authority for the purposes of search.
3. 🔲	In addition, in the case that more than one version or copy of a sequence listing and/or table(s) relating thereto has been filed or furnished, the required statements that the information in the subsequent or additional copies is identical to that in the application as filed or does not go beyond the application as filed, as appropriate, were furnished.
4. Addi	itional comments:

Form PCT/ISA/237(Box No. I) (April 2005)

Form PCT/ISA/237 (Box No. V) (April 2005)

International application No. PCT/IL06/00453

Box No. V Reasoned statement under Rule 4 applicability; citations and explan	3 <i>bis</i> .1(a)(i) vations suppo	ith regard to novelty, inventive step or in ting such statement	lustrial
1. Statement			
	Claima	11	YES
Novelty (N)	Claims	-41 IONE	
	Ciaims	NONE	
· · · · · · · · · · · · · · · · · · ·	Claims	IONE	YES
Inventive step (IS)	Claims		NO
•	Otalina		
Industrial applicability (IA)	Claims	-41	YES
moustrial approaching (Claims		NO
2. Citations and explanations:			
Please See Continuation Sheet			
•	•		
•			
		•	
•			
·			•
•			
•			
	*	•	

International application No. PCT/IL06/00453

Supplemental Box In case the space in any of the preceding boxes is not sufficient.	

V. 2. Citations and Explanations:

Claims 1-5,7-10,12-33, and 34-41 lack an inventive step under PCT Article 33(3) as being obvious over US Patent No. 6,389,552 of Hamilton et al referred hereinafter "Hamilton" in view of Patent Application Publication 2003/0097607 of Bessire.

In regards to claims 1,22,23,24, and 41 Hamilton discloses:

accepting data for storage from one or more data sources (see column 2 lines 45-55)

sending the data for storage in a primary storage device and in a secondary storage device (see column 2 lines 45-55) when an event damaging at least some of the data in the primary storage device occurs, reconstructing the data using at least part of the data stored in the secondary storage device (see column 3 lines 25-33)

However, Hamilton fails to explicitly disclose:

while awaiting an indication of successful storage of flag data in the secondary storage device, temporarily storing a record associated with the data in a disaster-proof storage unit adjacent to the primary storage device and using the record stored in the disaster proof storage unit for reconstruction during event damaging.

Bessire discloses while awaiting an indication of successful storage of flag data in the secondary storage device, temporarily storing a record associated with the data in a disaster-proof storage unit adjacent to the primary storage device and using the record stored in the disaster proof storage unit for reconstruction during event damaging (see page 3-4 paragraph 32 and 38).

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton and Bessire such that while awaiting an indication of successful storage of flag data in the secondary storage device, temporarily storing a record associated with the data in a disaster-proof storage unit adjacent to the primary storage device and using the record stored in the disaster proof storage unit for reconstruction during event damaging. A person of ordinary skill in the art would have been motivated to combine the teachings because Hamilton is concerned with recovering data during a disaster (see column 3 lines 53-55) and temporarily storing a record associated with the data in a disaster-proof storage unit, as per teachings of Bessire, enables recovery of data being transferred during a failure without having the data source retransmit the data (see page 4 paragraph 38).

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

In regards to claim 2, Bessire discloses:

sending an acknowledgement to the one or more data sources responsively to a successful caching of the record in the disaster-proof storage unit, without waiting to receive the indication of the successful storage of the data in the secondary storage device, so as to reduce a transaction latency associated with the storage of the data (see page 4 paragraph 38).

In regards to claim 3, Bessire discloses:

wherein temporarily storing the record comprises receiving an acknowledgement from the secondary storage device acknowledging the successful storage of the data in the secondary storage device, and deleting the record from the disaster-proof storage unit responsively to the acknowledgement (see page 4 paragraph 38).

In regards to claim 4, Bessire discloses:

wherein reconstructing the data comprises retrieving the disaster-proof storage unit following the event, extracting the record from the disaster proof storage unit and writing the data associated with the record to the secondary storage device (see page 3 paragraph 32).

In regards to claim 5, Bessire discloses:

wherein writing the data comprises remotely connecting the disaster-proof storage unit to the secondary storage device (see page 3 paragraph 32).

In regards to claim 7, Bessire discloses:

detecting the event using a detection mechanism in the disaster proof storage unit and modifying operations of the disaster proof storage unit responsive to detecting the event (see page 3 paragraph 32).

In regards to claim 8, Bessire discloses:

wherein the event comprises detecting at least one of a loss of external power supply and communication failure at the disaster proof storage unit (see page 3 paragraph 32).

In regards to claim 9, Hamilton discloses:

wherein modifying the operation comprises transmitting the record from the disaster-proof storage unit over a wireless communication link (see column 2 lines 35-40).

In regards to claim 10, Bessire discloses:

wherein temporarily storing the record comprises storing the record in two or more disaster proof storage units, wherein transmitting the record comprises transmitting two or more different parts of the record respectively from the two or more disaster proof-storage units over respective links so as to shorten transmission time of the record (see page 3 paragraph 31) Furthermore, Hamilton discloses using a wireless link (see column 2 lines 35-40). In regards to claims 12 and 25, Hamilton discloses: sensing an environment condition using an environmental sensor, predicting the event responsively to the sensed environmental conditions (see column 3 lines 23-33).

Bessire also discloses after predicting the event, transmitting the record from the disaster-proof storage unit using at least one of a wired connection and a wireless connection (see page 3 paragraph 32).

In regards to claim 13, Hamilton discloses:

wherein sensing the environmental condition comprises accepting a manual indication from a user that indicates the event (see column 3

In regards to claim 14, Bessire discloses:

wherein temporarily storing the record comprises sending an acknowledgement message responsively to a successful storage of the record in the disaster-proof storage unit, and comprising, after predicting the event, refraining from sending subsequent acknowledgement messages so as to avoid accepting additional data from the one or more data sources (see page 4 paragraph 38).

In regards to claim 15, Hamilton discloses:

refraining from sending subsequent data for storage in primary storage device (see column 3 lines 25-33).

In regards to claim 16, Bessire discloses:

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

after predicting the event, temporarily storing in the disaster-proof storage unit only subsequent records associated with data originating from a subset of the one or more data sources (see page 4 paragraph 38).

In regards to claim 17, Bessire discloses:

wherein temporarily storing the record comprises avoiding exceeding a memory capacity in the disaster-proof storage unit by matching the memory capacity with at least one of a maximum allowed size of data pending for acknowledgement by the second storage device and a maximum number of write commands pending for storage in the secondary storage device (see page 4 paragraph 38).

In regards to claim 18, Bessire discloses:

wherein temporarily storing the record comprises including in the record additional information related to the data, the additional information comprising at least one of an address of an originating data source, an address of the primary storage device, a time stamp indicating an acceptance time of the data and a storage address intended for the data in the primary storage device. Bessire disclose transmitting write request to storage (see page 4 paragraph 38). In order to know where in storage to write data, the data must include storage address information.

In regards to claim 19, Hamilton discloses:

accepting data for storage from one or more data sources (see column 2 lines 45-55) sending the data for storage in a storage device (see column 2 lines 45-55)

However, Hamilton fails to disclose:

temporarily storing records associated with at least a part of the data that is relevant to investigation of disaster events using the records stored in the disaster-proof storage unit and when an event damaging at least some of the data in the storage device occurs, investigating the event.

Bessire discloses:

temporarily storing records associated with at least a part of the data that is relevant to investigation of disaster events using the records stored in the disaster-proof storage unit and when an event damaging at least some of the data in the storage device occurs, investigating the event (see page 3-4 paragraph 32 and 38)

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton and Bessire temporarily storing records associated with at least a part of the data that is relevant to investigation of disaster events using the records stored in the disaster-proof storage unit and when an event damaging at least some of the data in the storage device occurs, investigating the event (see page 3-4 paragraph 32 and 38). A person of ordinary skill in the art would have been motivated to combine the teachings because Hamilton is concerned with recovering data during a disaster (see column 3 lines 53-55) and temporarily storing a record associated with the data in a disaster-proof storage unit, as per teachings of Bessire, enables recovery of data being transferred during a failure without having the data source retransmit the data (see page 4 paragraph 38).

In regards to claim 20, Bessire discloses:

wherein the at least part of the data that is relevant to investigation of disaster events comprises at least one of surveillance images, access control information, and data originating from a telephony system. Bessire discloses storing write I/O request, indicating access control information (see page 4 paragraph 38).

In regards to claim 21, Bessire discloses:

wherein at least part of the data that is relevant to investigation of disaster of events comprises data accepted at a time immediately preceding an occurrence of the event (see page 4 paragraph 38).

In regards to claim 26, Hamilton discloses:

a disaster-proof storage unit, which comprises:

a disaster-proof enclosure, which is arranged to protect components contained therein against disaster events (see column 2 lines 45-55)

control unit, which is arranged, when an event damaging at least some of the data in the primary storage device occurs, to provide the record so as to enable reconstruction of the data using at least part of the data stored in the secondary storage device (see column 3 lines

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

a sensor, which is arranged to sense an environmental condition in a vicinity of the primary storage device (see column 3 lines 23-33)

However, Hamilton fails to explicitly disclose:

a memory device contained in the enclosure, which is arranged to temporarily hold a record associated with the data while awaiting an indication of successful storage of the data in the secondary storage device and using the record stored in the memory device to enable reconstruction, and a protection processor, which is arranged to predict the event responsively to the sensed environmental condition and, responsively to predicting the event, to instruct the disaster-proof storage unit to transmit the record so as to protect the data. Bessire discloses a memory device contained in the enclosure, which is arranged to temporarily hold a record associated with the data while awaiting an indication of successful storage of the data in the secondary storage device and using the record stored in the memory device to enable reconstruction, and a protection processor, which is arranged to predict the event responsively to the sensed environmental condition and, responsively to predicting the event, to instruct the disaster-proof storage unit to transmit the record so as to protect the data (see page 3-4 paragraph 32 and 38).

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton and Bessire to use a memory device contained in the enclosure, which is arranged to temporarily hold a record associated with the data while awaiting an indication of successful storage of the data in the secondary storage device and using the record stored in the memory device to enable reconstruction, and a protection processor, which is arranged to predict the event responsively to the sensed environmental condition and, responsively to predicting the event, to instruct the disaster-proof storage unit to transmit the record so as to protect the data. A person of ordinary skill in the art would have been motivated to combine the teachings because Hamilton is concerned with recovering data during a disaster (see column 3 lines 53-55) and temporarily storing a record associated with the data in a disaster-proof storage unit, as per teachings of Bessire, enables recovery of data being transferred during a failure without having the data source retransmit the data (see page 4 paragraph 38).

In regards to claim 27, Bessire discloses:

wherein the control unit is arranged to delete the record from the memory device responsively to an acknowledgement from the secondary storage device acknowledging the successful storage of the data in the secondary storage device (see page 4 paragraph 38).

In regards to claim 28, Hamilton discloses:

wherein the control unit is arranged to communicate with the secondary storage device in order to provide the record so as to reconstruct the data (see column 3 lines 1-15).

In regards to claim 29, Bessire discloses:

wherein the memory device comprises at least one of a non-volatile memory and a removable memory (see page 3 paragraph 32).

In regards to claim 30, Bessire discloses:

wherein the control unit comprises a detection mechanism for detecting the event, and wherein the control unit is arranged to modify operation of the disaster-proof storage unit responsively to detecting the event (see page 3 paragraph 32).

In regards to claim 31, Bessire discloses:

wherein the detection mechanism is arranged to detect at least one of a loss of external electrical power supply and a communication failure at the disaster proof-storage unit (see page 3 paragraph 32).

In regards to claim 32, Hamilton discloses:

wherein the disaster-proof storage unit further comprises a wireless transmitter, which is arranged to transmit the record from the disaster-proof storage unit responsively to detecting the event (see column 2 lines 35-40)

In regards to claim 33, Bessire discloses:

wherein the disaster-proof storage unit is one of two or more disaster proof storage units, which are arranged to transmit respectively two or more different parts of the record over respective links so as to shorten transmission time of the record (see page 3 paragraph 31). Furthermore, Hamilton discloses using a wireless link (see column 2 lines 35-40). In regards to claim 35, Bessire discloses: wherein the record comprises additional information related to the data, the additional information comprising at least one of an address of an originating data source, an address of the primary storage device, a time stamp indicating an acceptance time of the data and a storage address intended for the data in the primary storage device. Bessire disclose transmitting write request to storage (see page 4 paragraph 38). In order to know where in storage to write data, the data must include storage address information.

International application No. PCT/IL06/00453

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

In regards to claim 36, Hamilton discloses:

wherein the sensor is arranged to accept a manual indication from a user so as to predict the event (see column 3 lines 1-15).

In regards to claim 37, Bessire discloses:

wherein the data is accepted from one or more data sources, and wherein protection processor is arranged to send an acknowledgement message responsively to a successful storage of the record in the disaster-proof storage unit, and to refrain from sending subsequent acknowledgement messages so as to avoid accepting additional data from the one or more data sources (see page 4 paragraph 38).

In regards to claim 38, Bessire discloses:

wherein the data is accepted from one or more data sources, and wherein the protection processor is arranged to control a rate of the data accepted from the one or more data sources after predicting the event (see column 3 lines 25-33

In regards to claim 39, Bessire discloses:

wherein the data is accepted form one or more data sources, and wherein the protection processor is arranged to send for temporary storage in the disaster-proof storage only subsequent records associated with data originating from a subset of the one or more data sources after predicting the event (see page 4 paragraph 38).

In regards to claim 40, Bessire discloses:

wherein a capacity of the memory device is matched to a maximum allowed size of data pending for acknowledgement by the secondary storage device so as to avoid exceeding the memory capacity (see page 4 paragraph 38).

Claim 6 lacks an inventive step under PCT Article 33(3) as being obvious over Hamilton in view of Bessire and in further view of 2004/0059844 of Jones et al. referred hereinafter "Jones".

In regards to claim 6, Hamilton in view of Bessire fails to disclose:

wherein the disaster proof storage unit comprises a removable memory device for holding the record, and wherein reconstructing the data comprises when the disaster proof storage unit is damaged by the event, removing the memory device from the disaster proof storage unit and installing the memory device in another unit for readout of the record.

However, Jones discloses in the event of a failure to any portion of the module, the Removable Memory Unit is removed from the module and connected to a new module (see page 2 paragraph 11), indicating wherein the disaster proof storage unit comprises a removable memory device for holding the record, and wherein reconstructing the data comprises when the disaster proof storage unit is damaged by the event, removing the memory device from the disaster proof storage unit and installing the memory device in another unit for readout of the record.

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton, Bessire, and Jones to have a removable memory device for holding the record, and wherein reconstructing the data comprises when the disaster proof storage unit is damaged by the event, removing the memory device from the disaster proof storage unit and installing the memory device in another unit for readout of the record. A person of ordinary skill in the art would have been motivated to combine the teachings because Bessire discloses a memory device for temporarily storing data for recovery (see page 3 paragraph 32), and having a removable memory device constitute a suitable memory device that enables connectable to a new module upon failure of a current module (see page 2 paragraph 11), thus enabling recovery even when there is a failure to the module.

Claims 11 and 34 lack an inventive step under PCT Article 33(3) as being obvious over Hamilton in view of Bessire and in further view of 2003/0204597 of Arakawa et al. referred hereinafter "Arakawa".

In regards to claims 11 and 34, Hamilton in view of Bessire fails to disclose:

wherein modifying the operations comprises transmitting a homing signal from the disaster proof storage unit, so as to enable location and retrieval of the disaster proof storage unit.

However, Arakawa discloses when a storage subsystem detect a failure, sending notification of the failure (see page 8 paragraph 112), indicating wherein modifying the operations comprises transmitting a homing signal from the disaster proof storage unit, so as to enable location and retrieval of the disaster proof storage unit.

It would have been obvious to one of ordinary skill in the art at the time of the invention to combine the teachings of Hamilton, Bessire, and Arakawa such that when a storage subsystem detect a failure, sending notification of the failure, indicating wherein modifying the

International application No. PCT/IL_06/00453

INTERNATIONAL SEARCHING AUTHORITI					
Supplemental Box In case the space in any of the preceding boxes is not sufficient.					
operations comprises transmitting a homing signal from the disaster proof storage unit, so as to enable location and retrieval of the disaster proof storage unit. A person of ordinary skill in the art would have been motivated to combine the teachings because Hamilton is concerned with recovering from a failure of a data storage device (see column 3 lines 23-33) and sending notification of a failure, as per teaching of Arakawa (see page 8 paragraph 112), constitute a suitable and known means to identifying a failure of the data storage device, thus enabling recovery from failure. Claims 1-41 meet the criteria set out in PCT Article 33(4), and thus have industrial applicability because the subject matter claimed can					
be made or used in industry.					
•					
•					